



August 8, 2025
Our 96th Year

Ship To:
BIRMINGHAM, AL 35242
US

Bill To:
BIRMINGHAM, AL 35242
US

Attn:
Phone: 816-676-4098
Email:

Altec Sales Order:
Altec Quotation Number:
Run Number:
Account Manager: Start
Technical Sales Rep:
Reference WO:
Customer Inspection:
Customer Truck Number:

X7 Discrete Job:
X7 Configured Item: 1
Quantity: Evan Sandidge
X4 Discrete Job:
X4 Configured Item:
System Engineer:
Structural Engineer: Evan Sandidge
Line Set Date: 08/27/2024

Item	Description	Qty
	Unit	
1.	DT65, Hydraulic Derrick, designed for mounting over the rear axle, in accordance with the standard specifications and to include the following features	1
2.	Rear Mount	1
3.	Subbase For DT65 With Radial Outriggers On Standard Chassis	1
4.	Outriggers	1
5.	Turntable Winch	1
6.	15k Single Speed Planetary Winch	1
7.	175 - Digger Derrick Use Only (NO Personnel Handling)	1
8.	Right Hand Digger Storage	1
9.	15K Two Speed HydraSync Digger Drive System	1
10.	Boom Tip Sheaves for Synthetic Load Line	1
11.	Foot Throttle	1
12.	No Tool Circuit at Boom Tip	1
13.	Pole Guides And Transferable Flares	1
14.	134 - Altec Rotafloat System	1
15.	Pole Guide Tongs For 24 In Dia Pole Maximum	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
16.	Pedestal-Mounted Ring Steps For Riding Seat Access	1
17.	2.63 in Hex Output Shaft With 2.63 in Hex Extension Shaft	1
18.	Hydraulic Side Load Protection: relieves overload conditions by allowing rotation system to back drive.	1
19.	Full-View, Single T-handle Riding Seat with Pilot Operated Controls	1
20.	Manual Hydraulic Outrigger Controls	1
21.	Capacity Chart DT65 THD (With Digger)	1
22.	Altec Powder Paint Process	1
23.	Base Boom and Turntable Painted White (Standard)	1
24.	Subbase Painted Black (Standard)	1
25.	Upper Booms Painted White (Standard)	1
26.	Outrigger Legs Painted White (Standard)	1
<u>Unit and Hydraulic Acc.</u>		
27.	Dirt Auger, 24 Inch DIA, With 2-5/8 Inch Hex X 104 Inch Long (Painted Black)	1
28.	Synthetic Rope, 150 FT Of 1" Diameter	1
29.	DT65 Subbase Installation Components	1
30.	Load Line Swivel Hook, 8-1/2 Ton	1
31.	HVI-22 Hydraulic Oil (Standard).	120
32.	100 Gallon Reservoir With Sight Gauge	1
33.	Standard Pump For PTO	1
34.	Hot shift PTO for automatic transmission	1
35.	Standard Altec PTO/Transmission Functionality with Park Brake Auto Neutral for Allison Automatic Transmissions: -Once the PTO switch is on, the Parking Brake is engaged, and the transmission is in a near stationary condition (i.e., below 5 mph) the transmission will be forced to neutral, and PTO will engage.	1
36.	Altec recommends any connection made to the tool circuit be done with Non-Conductive hose. If ordering a Hose reel, Altec recommends ordering a hose reel with Non-Conductive hose. The lower tool circuit hoses may be, or become, conductive. Death or serious injury could occur if the unit becomes energized while lower tool circuit is in use.	1
37.	Spring Loaded Hose Reel, 50 FT Hose Capacity	1

Sales Text: Installed on tailshelf offset to streetside

Last Updated By: Leslie J Handley on 27-FEB-2024 14:10

<u>Item</u>	<u>Description</u>	<u>Qty</u>
38.	Install Tool Circuit For Hose Reel Installation, Below Rotation (Male Pressure, Female Return -Installed at Hose Reel)	1
39.	50' Non-Conductive Hose Kit, Orange, Includes Quick Disconnects and Dust Caps (Male Pressure, Female Return)	1
<u>Body</u>		
40.	161 inch Flatbed, suitable for installing on any 6x6 chassis with an approximate CT dimension of 150-152 inches, built to the following specifications:	1
	<ul style="list-style-type: none"> A Basic flatbed fabricated from hot rolled steel. . Possible contact edges are folded for safety. B Steel treated for improved primer bond and rust resistance. . Automotive undercoating applied to entire underside of flatbed. C Primer applied to complete top side of flatbed. . Finish paint flatbed Altec White at body manufacturer. D All steel flatbed, 161 inches long x 96 inches wide. . Floor made from 9/64 inch (10 gauge) thick smooth galvalume. E Frame built with 4 inch high structural channel. . 2.25 inch high x .25 inch thick rub rail installed on sides of flatbed. F Stake pockets around outside perimeter of flatbed, with 5.5 inch high stake retainer assemblies on sides. G Gripstrut recessed access steps on curbside. Includes one (1) U-shaped grab handle and one (1) folding step below access steps H 2 inch x 6 inch drop-in wooden cargo retaining board at top of side access steps. . Six (6) recessed D-rings installed in flatbed floor, three (3) located on each side. I 27 inch long steel tailshelf, width to match flatbed. Includes stake pockets and 5.5 inch high removable stake rails at sides and rear. Includes curbside grab handles and cutout for FA provided recessed access ladder attached to rear outrigger. . Outrigger trap door on both sides of flatbed. K Two (2) post-style grab handles installed at the curbside ladder cutout. . Four (4) 25 inch x 25 inch x 5 inch outrigger pad holders. Includes wheel chock holder on each pad holder. 	
	L	
	.	
	M	
	.	
	N	
	.	
	O	
	.	
	P	
	.	
	Q	
	.	
	R	
	.	
41.	42 inch saddle box, suitable for installing on any 6x6 chassis, built to the following specifications:	1
	A C.	
	.	
	B	
	.	
	D.	
	E.	



- body fabricated from A40 grade 100% zinc alloy steel.
- G** All doors are full, double paneled, self-sealed with built-in drainage for maximum weather-tightness. Stainless steel hinge rods extend full length of door.
 - H** All doors are to contain stainless steel flush type, single point, two-stage rotary paddle latches with recessed handles, including keyed locks and strikers. Door latches are bolted to the outer door panel.
 - I** Possible contact edges are folded for safety.
 - J** Integrated door header drip rail at top for maximum weather protection.
 - K** Steel treated for improved primer bond and rust resistance.
 - L** Automotive undercoating applied to entire underside of body.
 - M** Primer applied to complete interior and exterior of body.
 - N** Automotive type non-porous door seals fastened to the door facing.
 - O** 42 inch overall T-box length.
 - P** 96 inch overall T-box width.
 - Q** 52 inch overall T-box height.
 - R** 18 inch T-box compartment depth.
 - S** Finish paint body Altec White at body manufacturer.
 - T** Gas shock type rigid door holders for vertical doors.

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You
UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>
P	Standard master body locking system.	
.	Full transverse compartment extending through the curbside vertical. Includes	
Q	transverse shelf.	
.	1st vertical streetside (LH) - Four (4) locking swivel hooks on adjustable rails. 2-0-2 configuration.	
R	2nd vertical streetside (LH) - Six (6) locking swivel hooks on adjustable rails. 2-2-2 configuration.	
.	1st vertical curbside (RH) - Four (4) locking swivel hooks on adjustable rails. 2-0-2 configuration.	
S	2nd vertical curbside (LH) - Six (6) locking swivel hooks on adjustable rails. 2-2-2 configuration.	
T	One (1) grab handle installed at the rear of the curbside compartment.	
.	One (1) 96 inch long x 12 inch high x 22 inch wide open top punched metal box. Installed using B-line on top of transverse compartment.	
U	2 inch x 6 inch drop-in wooden cargo retaining board at rear of T-box	
.		
	<u>Body and Chassis Accessories</u>	
V		
.		
W		
.		
X		
.		
42.	Underride Protection Bumper Installed At Rear	1
43.	Swivel Style Pintle Hitch (30 000 LB MGTW with 6 000 LB MVL), 11-Bolt T-Mount, Altec Preferred (T-125 Style)	1
44.	Set Of D-Rings for Trailer Safety Chain, installed one each side of towing device mount.	1
45.	Relocate Chassis-Supplied Glad Hands	1
	<u>Sales Text: rear</u>	
	Last Updated By: Noah DeWeese Hr Auto-Ended on 12-FEB-2025 13:58	
46.	Access Ladder, Deploys with Outrigger, Curbside Rear	1
47.	Boom Rest	1
48.	Mounting Brackets for Lights, Located on Lower Boom Rest	1
49.	Wood Outrigger Pad, 24 x 24 x 2.5 Inch, With Rope Handle	4
50.	Mud Flaps With Altec Logo (Pair)	1
51.	Wheel Chocks, Rubber, 9.75" L x 7.75" W x 5.00" H, with 4" L Metal Hairpin Style Handle (Pair)	1
52.	Wheel Chock Holders (Pair), Single Capacity, With Mudflap Mounting, For Installation Under Flatbed Or Dump Body	1
53.	Slope Indicator Assembly (Pair) For Machine With Outriggers	2
54.	Triangular Reflector Kit (Contains 3 Reflectors), Shipped Per DEPS-0042	1
55.	5 LB Fire Extinguisher With Light Duty Bracket, Installed (In Cab or Inside Compartment Only)	1
56.	57.	



58. Ateco for storage of all operator and parts manuals	1
Outrigger Control Guards- Underhung Tailshelf Mount	1
Outrigger Flap Retaining Lanyards Installed (Pair)	1

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You
UTILITY EQUIPMENT AND BODIES SINCE 1929

<u>Item</u>	<u>Description</u>	<u>Qty</u>
<u>Electrical Accessories</u>		
59.	Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)	1
60.	Altec Standard Amber LED Strobe Light with Brush Guard	2
Sales Text: Install one (q) each side of boomstow Last Updated By: Leslie J Handley on 27-FEB-2024 14:10		
61.	Remote Spot Light, LED, Permanent Mount, With Wireless Dash Mounted Controls And Programmable Wireless Remote (Go-Light #20074GT)	2
Sales Text: Mount One (1) each side of boom stow Last Updated By: Leslie J Handley on 03-MAR-2025 15:21		
62.	Dual Tone Back-Up With Outrigger Motion Alarm	1
63.	Altec Standard Multi-Point Grounding System	6
64.	Copper U Shaped Grounding Lug (Threaded)	2
Sales Text: Install one (1) curbside front and one (1) curbside rear Last Updated By: Leslie J Handley on 27-FEB-2024 14:10		
65.	PTO Hour Meter, Digital, with 10,000 Hour Display	1
66.	7-Way Trailer Receptacle (Pin Type) Installed At Rear	1
67.	Relocate Trailer Receptacle Supplied With Chassis	1
68.	Electric Trailer Brake Controller (Draw-Tite Activator II #5504)	1
69.	Altec Modular Panel System (AMPS) - Includes Mounting Panel and Accessory Switches	1
70.	Pre-Wired Power Distribution Module - Installed	1
71.	Additional Sold Stock And Global Option	2
Sales Text: Adhesive Strip Lighting, LED, Installed Around Top And Sides Of Compartment Door Facings In Body (Installed At Final Assembly) (Industry Preferred) in Saddle Box Last Updated By: Leslie J Handley on 03-MAR-2025 15:21		
<u>Finishing Details</u>		
72.	Powder Coat Unit Altec White	1
73.	Altec Standard; Components mounted below frame rail shall be coated black by Altec. i.e. step bumpers, steps, frame extension, pintle hook mount, dock bumper mounts, D-rings, receiver tubes, accessory mounts, light brackets, under-ride protection, etc. Components mounted to under side of body shall be coated black by Altec. i.e. Wheel chock holders, mud flap brackets, pad carriers, boxes, lighting brackets, steps, and ladders.	1
74.	Apply Non-Skid Coating to all walking surfaces	1

<u>Item</u>	<u>Description</u>	<u>Qty</u>
75.	Apply Non-Skid Coating to Curbside Compartment Top for use as a Non-Walking Surface	1
76.	Apply Non-Skid Coating to Streetside Compartment Top for use as a Non-Walking Surface	1
77.	Globalization includes Unit Condition Report and Placards	1
78.	English Safety And Instructional Decals	1
79.	Vehicle Height Placard - Installed In Cab	1
80.	Placard, HVI-22 Hydraulic Oil	1
81.	DOT Certification Required	1
<p>Sales Text: 33 Inverness Center Parkway Birmingham AL 35242 Last Updated By: Leslie J Handley on 27-FEB-2024 14:10</p>		
82.	Dielectric test unit according to ANSI requirements.	1
83.	Stability test unit according to ANSI requirements.	1
84.	Completed Test Forms To Be Included In The Manual Pouch	1
	<ul style="list-style-type: none"> A. Stability Test Form B. Dielectric Test Form (For Insulating Units) 	
85.	Focus Factory Build	1
86.	Globalized Per Global Rental's Specification To Include Following:	1
	<ul style="list-style-type: none"> A Global Key Rings Installed on Keys . Global Decal Kit B Full Discrete Job Numbers Located on Front Streetside and Curbside Rear of Vehicle . Vehicle C Fuse Kit in the Manual Pouch . Completed Service Sticker Located Next to the DOT Sticker Weight Slip D Signed/Dated Dielectric and Stability Test . Completed Unit Condition Reports E Four (4) Pictures Showing the Front, Rear, Curbside and Streetside of the Full Truck . Truck F Temp Tag . G . H . I . J . 	

87. 89.

88.

As Built Electrical And Hydraulic Schematics To Be Included In The Manual Pouch

Altec Stock/Global Spec, DT65H, Freightliner M2-106 6x6 Automatic

Chassis

Altec Supplied Chassis

2025 Model Year

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You
UTILITY EQUIPMENT AND BODIES SINCE 1929

Item	<u>Description</u>	<u>Qty</u>
92.	Freightliner M2-106	1
93.	Dual Rear Wheel	1
94.	Set Back Axle	1
95.	6x6 Tandem Axle	1
96.	Chassis Cab	1
97.	Regular Cab	1
98.	Chassis Color - White	1
99.	Chassis Without Front Frame Extensions	1
100.	Air Horn Under Cab	1
101.	AM/FM Radio	1
102.	Bluetooth	1
103.	Block Heater	1
104.	Driver Controlled Locking Differential	1
105.	Glad Hands, Hoses And Connections (Supplied By Chassis OEM)	1
106.	Trailer Air Brake Package	1
107.	Air Conditioning	1
108.	Cruise Control	1
109.	Tachometer	1
110.	151 Clear CA (Round To Next Whole Number)	1
111.	Chassis Wheelbase Length - 220	1
112.	GVWR 56,000 LBS	1
113.	16,000 LBS Front GAWR	1
114.	40,000 LBS Rear GAWR	1
115.	17.01 - 18.00 Section Modulus	1
116.	Spring Suspension	1
117.	Cummins L9	1
118.	Diesel	1
119.	330 HP Engine Rating	1
120.	Allison 3500 RDS Automatic Transmission (Left and Right Side PTO Openings Only)	1

Item	Description	Qty
121.	204-215 Freightliner 50 Gallon Fuel Tank (Left Hand Under Cab)	1
122.	23U-001, 43X-002 Freightliner 6 Gallon DEF Tank (Under Cab Left Hand)	1
123.	016-1C2 - Freightliner Vertical Exhaust (Right-Horizontal-Under Cab-Vertical)	1
124.	CARB Clean Idle Certification	1
125.	50-State Emissions	1
126.	No Idle Engine Shut-Down Required	1
127.	Air Brakes	1
128.	Park Brake In Rear Wheels	1
129.	2 Chassis Batteries	1
130.	Other Battery Capacity (CCA)	1

Sales Text: .

Last Updated By: Leslie J Handley on 03-OCT-2023 16:47

131.	Battery Under Cab Left Hand	1
132.	Freightliner - Clear Area Around Allison PTO Openings (362-824) and (363-011)	1
133.	Freightliner - Electric Brake Controller Wiring With Combined Stop/Turn Signal Heavy Duty Tail Light Wiring At EOF (296-027)	1
134.	Freightliner - Radiator (1100 Square Inch) for ISL/L9 or DD8.2 (DS) (266-013)	1
135.	Freightliner - Rear Cab Crossmember Flush With Back Of Cab (561-010)	1
136.	Freightliner PTO Throttle Wiring for Automatic Transmission with Pre-Wire (163-001), (148-074), (87L-003)	1
137.	Freightliner Transmission Dipstick Tube Enters Curbside of Transmission (346-013)	1
138.	Freightliner/Allison Body Builder Connection with Pre-Wire (34C-002)	1
139.	Freightliner - Pre-Wire Chassis with Cab Backwall Pass-Thru (33U-001)	1
140.	Vinyl Split Bench Seat	1

Additional Pricing

141.	Standard Altec Warranty: One (1) year parts warranty, one (1) year labor warranty, ninety (90) days warranty for travel charges, limited lifetime structural warranty	1
142.	Federal Excise Tax Item: If provided, Quote subtotal is an Estimate only. Final determined at invoicing.	1

Miscellaneous

143.	Global Spec Modification	1
------	--------------------------	---

Quote Number: 1494585 - 2
Altec, Inc.

\$411,430
Delivery \$3,031
Estimate Total \$414,461

Altec Industries, Inc.

BY

Leslie J Handley , Technical Sales Representative

<u>Item Number</u>	<u>Unselected Items</u> <u>Description</u>
	<u>New Selected Items</u> <u>Description</u>
970625413-	Remote Spot Light, LED, Permanent Mount, With Wireless Dash Mounted Controls And Programmable Wireless Remote (Go-Light #20074GT) Mount One (1) each side of boom stow Created By:Leslie J Handley on 03-MAR-2025 15:21
970569131-	Additional Sold Stock And Global Option 31 (Electrical Accessories) Adhesive Strip Lighting, LED, Installed Around Top And Sides Of Compartment Door Facings In Body (Installed At Final Assembly) (Industry Preferred) in Saddle Box Created By:Leslie J Handley on 03-MAR-2025 15:21

We Wish To Thank You For Giving Us The Pleasure
And Opportunity of Serving You
UTILITY EQUIPMENT AND BODIES SINCE 1929